

PROSAFE BUSINESS WIRELESS ACCESS POINTS

MODEL	WG302	WAG102	WG102
Product Description	ProSafe 802.11g Wireless Access Point	ProSafe Dual Band Wireless Access Point	ProSafe 802.11g Wireless Access Point
Wireless Support	<ul style="list-style-type: none"> IEEE 802.11g 108 Mbps 	<ul style="list-style-type: none"> IEEE 802.11a IEEE 802.11g 108 Mbps on both bands 	<ul style="list-style-type: none"> IEEE 802.11g 108 Mbps
Frequency Rate	2.4 GHz	2.4 GHz and 5.0 GHz	2.4 GHz
PoE Port (built-in)	Yes	Yes	Yes
PoE Power Consumption	9 Watts	4.3 Watts	4.3 Watts
Wireless Distribution System (WDS)	<ul style="list-style-type: none"> Repeater Point-to-point/multi-point Simultaneous bridge & wireless client association 	<ul style="list-style-type: none"> Repeater Point-to-point/multi-point Separate bridge & access point 	<ul style="list-style-type: none"> Repeater Point-to-point/multi-point Separate bridge & access point
SSID	Single	Single	Single
SNMP	v1, v2c	v1, v2c	v1, v2c
Antenna	Two (2) 5 dBi detachable (2.4 GHz)	Two (2) 5 dBi detachable antennas (2.4 GHz and 5.0 GHz)	One (1) 5 dBi detachable (2.4 GHz)
User Support	Up to 128 users	Up to 128 users	Up to 64 users
Security	WPA2 – Enterprise, 802.11i	WPA2 – Enterprise, 802.11i	WPA2 – Enterprise, 802.11i
WPA Support	Multiple	Multiple	Multiple
VPN Passthrough	Up to 256 users	Up to 256 users	Up to 256 users
MAC Address filtering	Yes	Yes	Yes
802.1x RADIUS	Yes	Yes	Yes
Block SSID Broadcast	Yes	Yes	Yes
Peer-to-peer blocking	Yes	Yes	Yes
Secure Socket Layer (SSL)	Yes	Yes	Yes
Remote management login	Yes	Yes	Yes
Secure SSH Telnet	Yes	Yes	Yes
QoS	Spectralink Support for Voice Priority		
Rogue AP Detection	Yes		Yes
IntelliFi RF Management			Yes
Ports	<ul style="list-style-type: none"> LAN Port: One (1) 10/100BASE-T Ethernet with IEEE 802.3af Power Over Ethernet (PoE) support Console Port: One (1) with standard RS-232C interface with DB-9 male connector Antenna Connectors: Two (2) reverse SMA 	<ul style="list-style-type: none"> LAN Port: One (1) 10/100BASE-T Ethernet with IEEE 802.3af Power Over Ethernet (PoE) support Antenna Connectors: Two (2) reverse SMA 	<ul style="list-style-type: none"> LAN Port: One (1) 10/100BASE-T Ethernet with IEEE 802.3af Power Over Ethernet (PoE) support Antenna Connectors: One (1) reverse SMA
Network Management	SNMP MIB I, MIB II, and 802.11 MIB	SNMP MIB I, MIB II, and 802.11 MIB	SNMP MIB I, MIB II, and 802.11 MIB
User Interface	Smart Wizard Install Assistant and browser-based interface	Smart Wizard Install Assistant and browser-based interface	Smart Wizard Install Assistant and browser-based interface
Remote Configuration	<ul style="list-style-type: none"> Web browser, SNMP or Telnet with command line interface (CLI) FTP with product line 	<ul style="list-style-type: none"> Web browser or SNMP 	<ul style="list-style-type: none"> Web browser or SNMP
Antennas Compatible	ANT2409, ANT2405, ANT24D18v2	ANT2409, ANT2405, ANT24D18v2	ANT2409, ANT2405, ANT24D18v2
Software Compatible	ProSafe NMS100	ProSafe NMS100	ProSafe NMS100
Physical Dimensions	25.4 x 17.8 x 3.18cm (10 x 7 x 1.25") Weight: 574g (1.27 lbs.)	14.1 x 10 x 2.7 cm (5.56 x 3.94 x 1.06") Weight: 386 g (.85 lbs.)	32 x 190.5 x 122 mm (1.25 x 7.5 x 4.8") Weight: .62 KG (1.3 lbs.)
Package Contents	<ul style="list-style-type: none"> Two (2) Detachable Antennas Resource CD Power Adapter Ethernet cable Wall Mounting Kit Installation guide Warranty/support information card 	<ul style="list-style-type: none"> Two (2) Detachable Antennas Resource CD Power Adapter Ethernet cable Installation guide Warranty/support information card 	<ul style="list-style-type: none"> One (1) Detachable Antenna Resource CD Power Adapter Ethernet cable Wall Mounting Kit Installation guide Warranty/support information card
Certifications	Wi-Fi Certified	Wi-Fi Certified	Wi-Fi Certified
Plenum-Rated	Yes	Yes	Yes
Warranty	3 Year	3 Year	3 Year
ProSupportMaintenance OnCall 24x7 XPressHW	PMB0331, PMB0311-100 PRR0331	PMB0331, PMB0311-100 PRR0331	PMB0331, PMB0311-100 PRR0331

